

P3000I

Compact & Lightweight



POWERRUSH

MORE STARTING CAPACITY ALLOWING YOU TO DO MORE WITH LESS.
 POWERRUSH increases electrical current upon demand, above rated output when starting electric motors

Single phase power

Power LTP	kW	2.50
Power COP	kW	2.30
Voltage	V	230
Frequency	Hz	50
Power factor	cos ϕ	1

Engine

Fuel	Petrol
Aspiration	Natural
Cooling System	Air
Starting system	Recoil

Consumption

Consumption at 75% of load	l/h	1.14
Tank capacity	l	4
Running time at 75% COP	h	3.5

Noise level

Acoustic power LWA	dB(A)	88
Acoustic pressure at 7m	dB(A)	61

Dimensions and weight

Length	(L) mm	565
Width	(W) mm	339
Height	(H) mm	467
Weight (dry)	Kg	27

Control Panel

Manual Start and Stop	•
Protection Control panel	IP 44
Economiser	•
Parallel kit receptacles	•
USB	•
Sockets	2 SCHUKO 230V 16A

Protection

Low oil level (oil guard)	•
Overload	•
Overvoltage	•
Overtemperature	•

• : Standard

- : Standard



The information is aligned with the Data file at the time of download. Printed on 12/03/2020 (ID 12072)

©2019 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice

